

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
MATIERE	INOSA	FT N° 71 V1

MSDS available

This is a through-coloured PVC wallcovering, printed using water-based inks, on a high-tear non-woven backing. Extra washable and impact resistant, this wallcovering is suitable for intensive use in public buildings. In line with regulations, it has B s2 d0 / Class A fire resistance rating. Quick and easy to hang. Simply paste the wall and align the edges of each strip.

**Description** 

Item codeINOS 9141...NameINOSARangeMATIERETypePVC wallcoveringPlainYes - 21 colours

Patterned No.

Composition

Type Compact PVC / Vinyl Type II
Backing High-tear non-woven backing

Ink Water-based printing inks

**Regulations - Environment** 

Fire rating B s 2 d0 / Class A EN 13501 / ASTM E-84

Acoustics Alpha w = 0,10 or 0,15 according to the substrate / acoustic report: PEUTZ - N°A3151

 Light fastness
 ≥ 7
 ISO 105

 VOCs
 A+
 ISO 16000

 CE marking
 DOP-CPR-NTLBN-26 / www.texdecor.com
 Norme EN 15 102

Manufactured by ISO 14001

Component PVC with no phthalate

Care Extra washable - scrubbable Standard EN 259
Use Intensive Standard EN 259

Packing - Packaging

Size of widths 130 cm +/- 3%

Length of roll 35 lm Partial sale to order Yes

Box size 1305 X 350 X350 mm = 35 ml

Weight of a roll 20 Kg (+/- 10%)

Hanging

Adhesive Ovalit TM - Quelyd Murale

Adhesive instructions Apply to the wall, using a roller

Quantity of adhesive +/- 200gr/m²
Match Free match
Hanging direction Invert strips

Seam Butt seam or double cut overlap

Removal Pelable